

nifty

RT

ROUGH TERRAIN WORK PLATFORMS

45ft, 50ft & 61ft
Platform heights

Exceptional Outreach
31ft - 43ft Working outreach

45% Gradeability
4WD for rough terrain

Suspension System
Improved traction on
uneven terrain

**Fully Proportional
Hydraulic Controls**
Simple, reliable &
easy to use

Platform Rotation & Jib
Improved access
to applications



niftylift.com



nifty RoughTerrain

With platform heights ranging from 45ft to 61ft, Nifty's **RT** Booms all come with impressive outreach capabilities as well as a host of other features designed to maximize their performance over the roughest terrain. Their innovative designs combine weight and space saving technology with the latest advances in boom geometry to create truly versatile, robust machines that are simple to use, easy to maintain and very economical to transport.



Compact chassis design and excellent turning circles mean they are extremely maneuverable on-site and with powerful 4WD available along with a unique suspension system, they provide superb traction on steep or uneven surfaces.



Fully proportional hydraulic controls deliver smooth and measured operation while platform rotation and a fly boom allow the operator to position the platform with precision, anywhere their vast working envelopes.

SPECIFICATIONS

	SP45 4x4	SP50 4x4	SP64 4x4
Working Height	50ft 10in	56ft 5in	68ft
Platform Height	44ft 3in	49ft 9in	61ft 3in
Working Outreach	31ft 6in	31ft 6in	41ft 4in
Slew	360°	360°	360°
Flyboom Arc	150°	150°	150°
Width	6ft 7in	6ft 7in	7ft 5in
Height	7ft 2in	7ft 2in	7ft
Length - Stowed	16ft 5in	16ft 5in	16ft 5in
- Overall	21ft 4in	21ft 4in	20ft 6in
Minimum Weight	14,110lbs*	14,330lbs*	13,700lbs*
Turning Radius - Outside	16ft 9in	16ft 9in	13ft
Platform Rotation	180°	180°	100°
Platform Capacity	500lbs	500lbs	500lbs
Platform Size	5ft 11in x 2ft 4in	5ft 11in x 2ft 4in	5ft 11in x 2ft 4in
Drive Speed	4.1mph	4.1mph	4.1mph
Gradeability	45%	45%	45%
Control System	Fully Proportional Hydraulic	Fully Proportional Hydraulic	Fully Proportional Hydraulic
Power System	Kubota 1505 32Hp	Kubota 1505 32Hp	Kubota 1505 32Hp

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

* Weights may vary according to specification / power options, please confirm before ordering.

Supplied by:

NIFTYLIFT INC

32 Concourse Way,
Greer, SC 29650 USA
Sales: 1-800-NIFTYLIFT (800-643-8954)
Office: 1-877-MYNIFTY (877-696-4389)
Fax: 1-864-968-8836
e.mail: info@niftylift.com
www.niftylift.com

NIFTYLIFT LTD

Fingle Drive, Stonebridge
Milton Keynes, MK13 0ER
England, United Kingdom
Tel.: +44 (0)1908 223456
Fax.: +44 (0)1908 312733
e.mail: info@niftylift.com
www.niftylift.com