

# nifty

## TrackDrive

### TRACK MOUNTED WORK PLATFORM

**34ft, 42ft & 50ft**  
Platform heights

**Superb Gradeability**  
Will climb very steep  
inclines as high as 60% (31°)

**Excellent Traction**  
Better grip on uneven terrain

**Fully Proportional  
Hydraulic Controls**  
Simple, reliable &  
easy to maintain

**Weight Saving Design**  
Lower cost transportation &  
better fuel economy on site

**Non-Marking Tracks**  
Optional rubber-free tracks  
available for indoor usage

**Variable Width Tracks**  
Access to narrow openings  
improving versatility



**niftylift.com**



# nifty TrackDrive

With platform heights of 33ft 6in, 42ft and 50ft 2in, Nifty's **TrackDrive** work platforms offer a range of capabilities to suit operator requirements.

The **TD34T** is available in two versions, the standard and narrow width machines (**TD34TN**). With 60% gradeability both offer excellent traction on steep or rough terrain and the narrow version will pass through a 2ft 6in opening for restricted access applications.

The **TD42T** offers exceptional all-round performance from such a compact and low weight base, and with a 500lbs safe-working-load, plenty of capacity for tools as well.

The **TD50** also provides an extremely impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4-wheel-drive self propelled platform would have difficulty.



TD50



TD34T

Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.



TD42T



TD34TN

Available on rubber-free urethane tracks.



Non-marking tracks

SPECIFICATIONS	TD34TN	TD34T	TD42T	TD50
<b>Working Height</b>	40ft	40ft	48ft 6in	57ft
<b>Platform Height</b>	33ft 6in	33ft 6in	42ft	50ft 6in
<b>Working Outreach</b>	20ft	20ft	25ft	28ft 7in
<b>Slew</b>	406°	406°	400°	360°
<b>Width - Traveling</b>	2ft 6in - 3ft 9in	3ft 7in	4ft 7in	6ft 1in
<b>- Working</b>	9ft 10in	11ft 8in	12ft 6in	14ft 4in
<b>Height</b>	6ft 3in	6ft 3in	6ft 7in	6ft 11in
<b>Length</b>	13ft	13ft	15ft 5in	18ft 4in
<b>Minimum Weight</b>	4,080lbs*	4,100lbs*	4,500lbs*	6,400lbs*
<b>Platform Capacity</b>	265lbs	500lbs	500lbs	500lbs
<b>Platform Size</b>	2ft 6in x 2ft 2in	3ft 7in x 2ft 2in	4ft 7in x 2ft 4in	3ft 7in x 2ft 2in
<b>Drive Speed</b>	1.0mph	1.0mph	1.3mph	1.3mph
<b>Gradeability</b>	60%	60%	45%	32%
<b>Control System</b>	Fully Proportional Hydraulic			
<b>Power System</b>	Diesel - Kubota 722 - 18hp			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

\* Weights may vary according to specification / power options, please confirm before ordering.

## Supplied by:

### NIFTYLIFT INC

32 Concourse Way,  
Greer, SC 29650 USA  
Sales: 1-800-NIFTYLIFT (800-643-8954)  
Office: 1-877-MYNIFTY (877-696-4389)  
Fax: 1-864-968-8836  
e.mail: info@niftylift.com  
www.niftylift.com

### NIFTYLIFT LTD

Fingle Drive, Stonebridge  
Milton Keynes, MK13 0ER  
England, United Kingdom  
Tel.: +44 (0)1908 223456  
Fax.: +44 (0)1908 312733  
e.mail: info@niftylift.com  
www.niftylift.com