niftylift



niftylift.com



nifty 120

12.33 m
40 ft 6 in
(A)

10.33 m
34 ft
(B)

5 m
16 ft 6 in
(C)

1,195 kg
2,630 lbs

200 kg
440 lbs

4%
2.1°

1.1 m x 0.65 m
3 ft 7 in x 2 ft 2 in

1.9 m
6 ft 3 in

1.1 m
3 ft 7 in

1.5 m
4 ft 11 in

2.7 m
8 ft 10 in

5.75 m
18 ft 10 in

D P

Bi-Energy





nifty 120T

12.2 m
40 ft
(A)

10.2 m
33 ft 6 in
(B)

6.1 m
20 ft
(C)

1,400 kg
3,100 lbs

200 kg
440 lbs

11%
6°

1.1 m x 0.65 m
3 ft 7 in x 2 ft 2 in

1.9 m
6 ft 3 in

1.1 m
3 ft 7 in

1.5 m
4 ft 11 in

3.55 m
11 ft 8 in

4.5 m
14 ft 9 in

Bi-Energy





nifty 150T

14.7 m
48 ft 6 in
(A)

12.7 m
42 ft
(B)

7.55 m
25 ft
(C)

1,775 kg
3,915 lbs

225 kg
500 lbs

23%
13°

1.4 m x 0.7 m
4 ft 7 in x 2 ft 4 in

2 m
6 ft 7 in

1.6 m
5 ft 3 in

3.8 m
12 ft 6 in

5.55 m
18 ft 3 in

Bi-Energy





nifty 170

17.1 m
56 ft
(A)

15.1 m
49 ft 6 in
(B)

8.7 m
28 ft 6 in
(C)

2,160 kg
4760lbs

200 kg
440 lbs

14%
8°

1.1 m x 0.65 m
3 ft 7 in x 2 ft 2 in

2.15 m
7 ft

1.65 m
5 ft 5 in

4.4 m
14 ft 5 in

6.2 m
20 ft 4 in

Bi-Energy





nifty 210

21 m
69 ft
(A)

19 m
62 ft 6 in
(B)

12 m
39 ft 6 in
(C)

3,495 kg
7,700 lbs

225 kg
500 lbs

17%
9.5°

100°

1.4 m x 0.7 m
4 ft 7 in x 2 ft 4 in

2.27 m
7ft 5 in

1.8 m
5 ft 11 in

4.3 m
14 ft 1 in

6.95 m
22 ft 10 in





nifty HR12LE

12.1 m
39 ft 6 in
(A)

10.1 m
33 ft
(B)

6.4 m
21 ft
(C)

2,540 kg
5,600 lbs

200 kg
440 lbs

1.2 m x 0.85 m
3 ft 11 in x 2 ft 9 in

1.98 m
6 ft 6 in

1.79 m
5 ft 11 in

3.97 m
13 ft

6 km/h
3.7 mph

3.63 m
11 ft 11in

25%
14°

All-**Electric**





nifty HR12NE

12.1 m
39 ft 6 in
(A)

10.1 m
33 ft
(B)

6.4 m
21 ft
(C)

3,480 kg
7,670 lbs

225 kg
500 lbs

1.2 m x 0.85 m
3 ft 11 in x 2 ft 9 in

1.98 m
6 ft 6 in

1.5 m
4 ft 11 in

3.97 m
13 ft

6 km/h
3.7 mph

3.3 m
10ft 10in

25%
14°

All-**Electric**
Diesel-**Electric**





nifty HR12 4x4

12.1 m
39 ft 6 in
(A)

10.1 m
33 ft
(B)

6.4 m
21 ft
(C)

3,450 kg
7,610 lbs

227 kg
500 lbs

1.2 m x 0.85 m
3 ft 11 in x 2 ft 9 in

1.99 m
6 ft 6 in

1.6 m
5 ft 3 in

4.05 m
13 ft 3 in

5 km/h
3.1 mph

3.45 m
11 ft 6 in

40%
22°

Hybrid²



nifty HR15N



15.5 m
51 ft
(A)

13.5 m
44 ft
(B)

9.7 m
32 ft
(C)

7,250 kg
15,980 lbs

227 kg
500 lbs

150°

180°

1.5 m x 0.8 m
4 ft 11 in x 2 ft 8 in

1.99 m
6 ft 6 in

1.5 m
4 ft 11 in

4.93 m
16 ft 2 in

6.4 m
21 ft

3.5 km/h
2.2 mph

3.5 m
11 ft 6 in

25%
14°

All-Electric
Hybrid²





nifty HR15E

15.7 m
51 ft 6 in
(A)

13.7 m
45 ft
(B)

9.4 m
31 ft
(C)

4,680 kg
10,320 lbs

227 kg
500 lbs

150°

180°

1.8 m x 0.85 m
5 ft 11 in x 2 ft 9 in

2.1 m
6 ft 11 in

2 m
6 ft 7 in

4.8 m
15 ft 9in

6.35 m
20 ft 10 in

6 km/h
3.7 mph

3.7 m
12 ft 2 in

35%
19°

All-**Electric**
Hydrogen-**Electric**



nifty HR15 4x4



15.7 m 51 ft 6 in (A)	13.7 m 45 ft (B)	9.4 m 31 ft (C)	4,500*/4,800 kg 9,920*/10,580 lbs
227 kg 500 lbs	150°	180°	1.8 m x 0.85 m 5 ft 11 in x 2 ft 9 in
2.1 m 6 ft 11 in	2 m 6 ft 7 in	4.8 m 15 ft 9 in	6.35 m 20 ft 10 in
6 km/h 3.7 mph	3.7 m 12 ft 2 in	45% 24°	D* Hybrid²





nifty HR17N

17 m 56 ft (A)	15 m 49 ft 6 in (B)	9.7 m 32 ft (C)	7,780 kg 17,155 lbs
227 kg 500 lbs	150°	180°	1.5 m x 0.8 m 4 ft 11 in x 2 ft 8 in
1.99 m 6 ft 6 in	1.5 m 4 ft 11 in	4.93 m 16 ft 2 in	6.4 m 21 ft
3.5 km/h 2.2 mph	3.5 m 11 ft 6 in	25% 14°	All-Electric Hybrid²



nifty HR17E



17.2 m 56 ft 6 in (A)	15.2 m 50 ft (B)	9.4 m 31 ft (C)	4,970 kg 10,960 lbs
227 kg 500 lbs	150°	180°	1.8 m x 0.85 m 5 ft 11 in x 2 ft 9 in
2.1 m 6 ft 11 in	2 m 6 ft 7 in	4.8 m 15 ft 9 in	6.35 m 20 ft 10 in
6 km/h 3.7 mph	3.7 m 12 ft 2 in	35% 19°	All-**Electric** Hydrogen-**Electric**





nifty HR17 4x4

17.2 m 56 ft 6 in (A)	15.2 m 50 ft (B)	9.4 m 31 ft (C)	5,000 kg 11,020 lbs
227 kg 500 lbs	150°	180°	1.8 m x 0.85m 5 ft 11 in x 2 ft 9 in
2.1 m 6 ft 11 in	2 m 6 ft 7 in	4.8 m 15 ft 9 in	6.35 m 20 ft 10 in
6 km/h 3.7 mph	3.7 m 12 ft 2 in	45% 24°	Hybrid²



nifty HR21E



20.8 m
68 ft 6 in
(A)

18.8 m
62 ft
(B)

13 m
42 ft 8 in
(C)

6,640 kg
14,640 lbs

250 kg
550 lbs

150°

160°

1.8 m x 0.8 m
5 ft 11 in x 2 ft 8 in

2.18 m
7 ft 2 in

2.27 m
7 ft 5 in

5.47 m
17 ft 11 in

6.62 m
22 ft

6 km/h
3.7 mph

3.89 m
12 ft 9 in

25%
14°

All-**Electric**



nifty HR21 4x4



20.8 m 68 ft 6 in (A)	18.8 m 62 ft (B)	13 m 42 ft 8 in (C)	6,680 kg 14,730 lbs
250 kg 550 lbs	150°	160°	1.8 m x 0.8 m 5 ft 11 in x 2 ft 8 in
2.18 m 7 ft 2 in	2.27 m 7 ft 5 in	5.47 m 17 ft 11 in	6.62 m 22 ft
6 km/h 3.7 mph	3.89 m 12 ft 9 in	45% 24°	Hybrid²



nifty HR22SE



21.7 m 71 ft (A)	19.7 m 65 ft (B)	18.8 m 62 ft (C)	9,980/10,220* kg 22,000/22,530* lbs
280 kg 620 lbs	150°	180°	2.4 m x 0.9 m 7 ft 10 in x 2 ft 11in
2.7 m 8 ft 10 in	2.49 m 8 ft 2 in	7.2 m 23 ft 7 in	9.09 m 29 ft 10 in
5.5 km/h 3.4 mph	7.72 m 25 ft 4 in	30% 17°	All-**Electric** Diesel-**Electric***





nifty HR28 4x4

28 m
92 ft
(A)

26 m
85 ft 6 in
(B)

19 m
62 ft
(C)

14,380*/14,460 kg
31,700*/31,880 lbs

280 kg
620 lbs

150°

180°

2.4 m x 0.9 m
7 ft 10 in x 2 ft 11in

2.7 m
8 ft 10 in

2.49 m
8 ft 2 in

7.3 m
23 ft 11 in

9.28 m
30 ft 5 in

4.7 km/h
3 mph

5.9 m
19 ft 4 in

35%*/40%
19°*/22°

* Hybrid²



nifty SD170 4x4



17.1 m
56 ft
(A)

15.1 m
49 ft 6 in
(B)

8.7 m
28 ft 6 in
(C)

2,750 kg
6,060 lbs

200 kg
440 lbs

9%
5°

1.1 m x 0.65 m
3 ft 7 in x 2 ft 2 in

2.2 m
7 ft 3 in

1.6 m
5 ft 3 in

4.4 m
14 ft 5 in

5.6 m
18 ft 4 in

8.3 km/h
5.2 mph

5.95 m
19 ft 6 in

30%
17°

Bi-Energy





nifty SD210 4x4x4

21.3 m 70 ft (A)	19.3 m 63 ft 6 in (B)	12.8 m 42 ft (C)	3,950 kg 8,700 lbs
227 kg 500 lbs	150°	100°	1.8 m x 0.85 m 5 ft 11 in x 2 ft 9 in
2.25 m 7 ft 5 in	2.05 m 6 ft 9 in	4.2 m 13 ft 9 in	6.15 m 20 ft 2 in
9 km/h 5.6 mph	3.5 m 11 ft 6 in	45% 24°	18% 10°



nifty TD120TN



12.2 m 40 ft (A)	10.2 m 33 ft 6 in (B)	6.1 m 20 ft (C)	1,890 kg 4,170 lbs
200 kg 440 lbs	13% 7.2°		1.1 m x 0.65 m 3 ft 7 in x 2 ft 2 in
1.95 m 6 ft 5 in	0.8 m 2 ft 7 in	1.15 m 3 ft 8 in	3 m 9 ft 10 in
4 m 13 ft 1 in	1.6 km/h 1 mph	60% 31°	D





nifty TD120T

12.2 m
40 ft
(A)

10.2 m
33 ft 6 in
(B)

6.1 m
20 ft
(C)

1,890 kg
4,170 lbs

200 kg
440 lbs

13%
7.6°

1.1 m x 0.65 m
3 ft 7 in x 2 ft 2 in

1.9 m
6 ft 3 in

1.1 m
3 ft 7 in

3.55 m
11 ft 8 in

3.95 m
13 ft

1.6 km/h
1 mph

60%
31°





nifty TD150T

14.7 m
48 ft 6 in
(A)

12.7 m
42 ft
(B)

7.55 m
25 ft
(C)

2,025 kg
4,500 lbs

225 kg
500 lbs

21%
12°

1.4 m x 0.7 m
4 ft 7 in x 2 ft 4 in

2 m
6 ft 7 in

1.4 m
4 ft 7 in

3.8 m
12 ft 6 in

4.7 m
15 ft 5 in

2.1 km/h
1.3 mph

45%
24°



IPAF

CE

Bi-Energy

Gen² Hybrid

All-Electric

HIRE ASSOCIATION EUROPE

Hae Member

www.hae.org.uk

nqa

ISO 9001

QUALITY MANAGEMENT

nqa

ISO 14001

ENVIRONMENTAL MANAGEMENT

nqa

ISO 45001

HEALTH & SAFETY MANAGEMENT

Niftylink®

1. 

2. 

	Nifty 120	Nifty 120T	Nifty 150T	Nifty 170	Nifty 210
1. [kN]	8.21	9.42	11.77	13.89	21.9
2. [kN/m²]	450	290	375	257	322

	SD170	SD210	TD120TN	TD120T	TD150T
1. [kN]	17.36	24.59	12.3	12.3	13.24
2. [kN/m²]	345	441	379	379	421

1. 

2. 

	HR12LE	HR12NE	HR12 4x4	HR15N	HR15E	HR15 4x4 (D)	HR15 4x4 (H)	HR17NE
1. [kN]	16.13	21.81	21.64	44.01	28.88	27.82	29.59	47.13
2. [kN/m²]	414	495	943	1294	781	752	800	1386

	HR17E	HR17 4x4	HR21E	HR21 4x4	HR22SE	HR22SDE	HR28 4x4 (B)	HR28 4x4 (H)
1. [kN]	30.59	30.77	40.55	40.79	60.39	61.8	86.29	86.76
2. [kN/m²]	827	832	1096	1102	889	910	1271	1278

niftylift



Niftylift Ltd

Chalkdell Drive, Shenley Wood,
Milton Keynes, MK5 6GF

☎ +44 1908 223456

info@niftylift.com

www.niftylift.com

THE KING'S AWARDS FOR ENTERPRISE
2024
INTERNATIONAL TRADE

All specifications are as guideline only and were correct at time of printing. Niftylift reserves the right to change any specification without notice. Weights stated are minimums and vary according to options, please confirm before ordering.

niftylift.com